

# IMPULSE/ BAG SEALING MACHINES

# BSE

## Saves your time and cost of packaging material

- Easy to operate
- Easy to maintain
- Economical in daily use
- Solid design
- Adjustable temperature
- Adjustable sealing speed
- Table model

## General technical Specifications

**Sealing width:** 2 – 8 mm.  
**Temperature:** 50° – 220°

**100**  
**200**  
**300**  
**400**  
**500**  
**600**

### BSE 100

**Welding length:** 100 mm.  
**Machine dimensions (LxWxH):** 150 x 60 x 90 mm.  
**Power:** 230 Volt, 50 Hz, 0.4 kW  
**Machine weight:** 2.4 kg.



### BSE 200

**Welding length:** 200 mm.  
**Machine dimensions (LxWxH):** 260 x 65 x 95 mm.  
**Power:** 230 Volt, 50 Hz, 0.4 kW  
**Machine weight:** 2.5 kg.



### BSE 300

**Welding length:** 300 mm.  
**Machine dimensions (LxWxH):** 370 x 70 x 100 mm.  
**Power:** 230 Volt, 50 Hz, 0.4 kW  
**Machine weight:** 2.6 kg.



### BSE 400

**Welding length:** 400 mm.  
**Machine dimensions (LxWxH):** 480 x 75 x 105 mm.  
**Power:** 230 Volt, 50 Hz, 0.4 kW  
**Machine weight:** 2.8 kg.



### BSE 500

**Welding length:** 500 mm.  
**Machine dimensions (LxWxH):** 590 x 80 x 110 mm.  
**Power:** 230 Volt, 50 Hz, 0.4 kW  
**Machine weight:** 3 kg.



### BSE 600

**Welding length:** 600 mm.  
**Machine dimensions (LxWxH):** 690 x 85 x 115 mm.  
**Power:** 230 Volt, 50 Hz, 0.4 kW  
**Machine weight:** 3.2 kg.

