

### Saves your time and cost of packaging material

- For heavy duty sealing and fastening applications
- Easy to operate
- Easy to maintain
- Economical in daily use
- Easy to carry around, net weight about 4.2 kg.
- Solid design
- Easy to adjust strapping tension
- Easy to adjust sealing time
- Comes with charger, adaptor and rechargeable battery, 3.0 Ah
- Optional additional battery

### General technical Specifications

<b>Sealing material:</b>	PP, PET Strapping belt, width 9 – 19 mm. Thickness 0.75 – 1.05 mm.
<b>Strapping tension:</b>	0 – 3300 N
<b>Packing capacity:</b>	2 – 5 strappings/min. depending on the operator

### MST 250

- Strapping procedure (3 steps):
  - 1) pulling
  - 2) sealing done by friction
  - 3) cutting



<b>Max. product size (WxH):</b>	no limit
<b>Min. product size (WxH):</b>	100 x 40 mm.
<b>Machine dimensions (LxWxH):</b>	450 x 100 x 130 mm.
<b>Power for charger:</b>	230 Volt, 50 Hz, 0.8 kW
<b>Weight of machine:</b>	3.2 kg.

### ACCU for MST 250

- Additional battery for MST 250

**Weight:** 1.0 kg.



## BAW 101 belt wagon

- Wagon for PET belt

**Core diameter:** Ø 406  
**Reel width:** 120 mm.  
**Weight:** 17 kg.



## BAW 102 belt wagon

- Wagon for PP belt

**Core diameter:** Ø 200  
**Reel width:** 200 mm.  
**Weight:** 18 kg.



## BAW 103 belt wagon

- Wagon for steel belt

**Core diameter:** Ø 406  
**Reel width:** 19 mm.  
**Weight:** 16 kg.

