

AUTOMATIC STRAPPING MACHINES

STR

Saves your time and cost of packaging material

- Easy to operate
- Easy to maintain
- Economical in daily use
- Easy to move around with 4 wheels fitted
- Solid design
- Easy to adjust strapping tension
- Optional frame sizes

General technical Specifications

Sealing material:

PP Strapping belt,
width 9 – 13 mm.
Thickness 0.5 – 0.8 mm.
Belt strapping
strength > 1500 N

Max. product weight:

200 kg.

Height of working table:

845 mm.

Strapping tension:

450 - 700 N

Packing capacity:

2 sec./ cycle, depending
on the operator

8040

8060

8080

12060

8040-A

8060-A

8080-A

12060-A

8060-AUTO-1

8060-AUTO-2

8060-AUTO-3

STR 8040

- Manual belt feed
- Manual product feed

Max. product size (WxH):

800 x 400 mm.

Min. product size (WxH):

80 x 50 mm.

Machine dimensions (LxWxH):

1420 x 760 x 1320 mm.

Power:

230 Volt, 50 Hz, 1.8 kW

Weight:

295 kg.



STR 8040-A

- Automatic belt feed
- Manual product feed

Max. product size (WxH):

800 x 400 mm.

Min. product size (WxH):

80 x 50 mm.

Machine dimensions (LxWxH):

1420 x 760 x 1320 mm.

Power:

230 Volt, 50 Hz, 1.8 kW

Weight:

295 kg.



AUTOMATIC STRAPPING MACHINES

STR

Saves your time and cost of packaging material

- Easy to operate
- Easy to maintain
- Economical in daily use
- Easy to move around with 4 wheels fitted
- Solid design
- Easy to adjust strapping tension
- Optional frame sizes

General technical Specifications

Sealing material:

PP Strapping belt,
width 9 – 13 mm.
Thickness 0.5 – 0.8 mm.
Belt strapping
strength > 1500 N
200 kg.
845 mm.
450 - 700 N
2 sec./ cycle, depending
on the operator

Max. product weight:

Height of working table:

Strapping tension:

Packing capacity:

8040

8060

8080

12060

8040-A

8060-A

8080-A

12060-A

STR 8060

- Manual belt feed
- Manual product feed

Max. product size (WxH): 800 x 600 mm.
Min. product size (WxH): 80 x 60 mm.
Machine dimensions (LxWxH): 1420 x 760 x 1520 mm.
Power: 230 Volt, 50 Hz, 1.8 kW
Weight: 300 kg.



STR 8060-A

- Automatic belt feed
- Manual product feed

Max. product size (WxH): 800 x 600 mm.
Min. product size (WxH): 80 x 60 mm.
Machine dimensions (LxWxH): 1420 x 760 x 1520 mm.
Power: 230 Volt, 50 Hz, 1.8 kW
Weight: 300 kg.



- 1 or 2 or 3 strap/ carton
- Automatic belt feed

STR 8060-AUTO with 1 sensor

Max. product size (WxH): 800 x 600 mm.
Min. product size (WxH): 80 x 60 mm.
Machine dimensions (LxWxH): 1420 x 760 x 1520 mm.
Power: 230 Volt, 50 Hz, 1.8 kW
Weight: 380 kg.



- Automatic product feed through machine controlled by sensors
- 1 meter driven infeed roller conveyor

STR 8060-AUTO with 2 sensors

Max. product size (WxH): 800 x 600 mm.
Min. product size (WxH): 80 x 60 mm.
Machine dimensions (LxWxH): 1420 x 760 x 1520 mm.
Power: 230 Volt, 50 Hz, 1.8 kW
Weight: 380 kg.

STR 8060-AUTO with 3 sensors

Max. product size (WxH): 800 x 600 mm.
Min. product size (WxH): 80 x 60 mm.
Machine dimensions (LxWxH): 1420 x 760 x 1520 mm.
Power: 230 Volt, 50 Hz, 1.8 kW
Weight: 380 kg.

Subject to change in technical specifications



ACLPACK
INTERNATIONAL

8060-AUTO-1
8060-AUTO-2
8060-AUTO-3

AUTOMATIC STRAPPING MACHINES

STR

Saves your time and cost of packaging material

- Easy to operate
- Easy to maintain
- Economical in daily use
- Easy to move around with 4 wheels fitted
- Solid design
- Easy to adjust strapping tension
- Optional frame sizes

General technical Specifications

Sealing material:

PP Strapping belt,
width 9 – 13 mm.
Thickness 0.5 – 0.8 mm.
Belt strapping
strength > 1500 N
200 kg.
845 mm.
450 - 700 N
2 sec./ cycle, depending
on the operator

Max. product weight:

Height of working table:

Strapping tension:

Packing capacity:

8040

8060

8080

12060

8040-A

8060-A

8080-A

12060-A

8060-AUTO-1

8060-AUTO-2

8060-AUTO-3

STR 8080

- Manual belt feed
- Manual product feed

Max. product size (WxH):

800 x 800 mm.

Min. product size (WxH):

80 x 80 mm.

Machine dimensions (LxWxH):

1420 x 760 x 1720 mm.

Power:

230 Volt, 50 Hz, 1.8 kW

Weight:

310 kg.



STR 8080-A

- Automatic belt feed
- Manual product feed

Max. product size (WxH):

800 x 800 mm.

Min. product size (WxH):

80 x 80 mm.

Machine dimensions (LxWxH):

1420 x 760 x 1720 mm.

Power:

230 Volt, 50 Hz, 1.8 kW

Weight:

310 kg.



AUTOMATIC STRAPPING MACHINES

STR

Saves your time and cost of packaging material

- Easy to operate
- Easy to maintain
- Economical in daily use
- Easy to move around with 4 wheels fitted
- Solid design
- Easy to adjust strapping tension
- Optional frame sizes

General technical Specifications

Sealing material:

PP Strapping belt,
width 9 – 13 mm.
Thickness 0.5 – 0.8 mm.
Belt strapping
strength > 1500 N
200 kg.
845 mm.
450 - 700 N
2 sec./ cycle, depending
on the operator

Max. product weight:

Height of working table:

Strapping tension:

Packing capacity:

8040

8060

8080

12060

8040-A

8060-A

8080-A

12060-A

STR 12060

- Manual belt feed
- Manual product feed

Max. product size (WxH):

1200 x 600 mm.

Min. product size (WxH):

120 x 60 mm.

Machine dimensions (LxWxH):

1820 x 760 x 1520 mm.

Power:

230 Volt, 50 Hz, 1.8 kW

Weight:

325 kg.



STR 12060-A

- Automatic belt feed
- Manual product feed

Max. product size (WxH):

1200 x 600 mm.

Min. product size (WxH):

120 x 60 mm.

Machine dimensions (LxWxH):

1820 x 760 x 1520 mm.

Power:

230 Volt, 50 Hz, 1.8 kW

Weight:

325 kg.



8060-AUTO-1

8060-AUTO-2

8060-AUTO-3